

## ITW Airbox I

The ITW GTR AirBox I allows you to fix tires within minutes without an annoying tire change. This innovative repair kit introduced by leading car manufacturers is connected to the damaged tire. Connect the sealant bottle hose to the tire and set the selector turn knob to "REPAIR". The compressor pumps instantly the sealant into the tire. Your damaged tire will be repaired in a simple, fast and clean within a few minutes without stress. Your trip to the next tire garage is now secured (many of our test rides last up to 1500km). ITW GTR sealant can be used for tire damages caused by nails, screws or similar up to 6mm in diameter either in the thread or the tire shoulder.

## ITW Airbox II

Description	Sealant	Bottle size	Operational Specs	Functions	Dimensions	Weight
Fully automatic single hose integrated system	SLX EG	450ml.	Mechanical operation durability: 500 cycles, full inflation, 3 min OFF time	<ul style="list-style-type: none"> <li>■ Full auto</li> <li>■ User interface on top</li> <li>■ Single hose</li> <li>■ Pictorial label with text</li> <li>■ Snap-together housing - no screws</li> </ul>	240mm x 160mm x 70mm 9 <sup>29</sup> / <sub>64</sub> " x 7 <sup>19</sup> / <sub>64</sub> " 2 <sup>3</sup> / <sub>4</sub> "	1.76kg. 3.89lb.



## General Specifications

Fill time, 0-3Bar (44PSI)	Avg. 7.3m. for 255/75R17
Operational temperature	-40° to 55° C **
Operating voltage	12 V nominal
Current	15 amp max.
Power cord	3277mm
Airhose length	660mm
Gauge	0-6 BAR (0-90Psi)
Gauge illumination	LED Backlit
Warranty	6 years
Standards met	Chrysler, Ford

**Cutting edge technology.  
Top notch quality.**

**ITW Global Tire Repair USA**  
125 Venture Drive, Suite 210,  
San Luis Obispo, CA 93401  
Toll Free (888) 457 - 5463  
Fax (805) 489-1920

**ITW Global Tire Repair Europe GmbH**  
Carl-Benz-Strasse 10, D-88696  
Owingen, Germany  
Tel. +49 (0) 7551 - 9200-0  
Fax +49 (0) 75 51 / 92 00 - 990