

## ITW Airbox II

The complete solution. This is our latest generation of full automatic solutions. The Airbox's patented design boasts the lightest weight and size of any full automatic solution on the market today. An integrated sealant bottle allows temporary repair of flat tires while the powerful pump takes care of inflation needs. Simply select the air setting for general inflation or the repair setting to get you back on the highway after a flat tire incident.

### ITW Airbox II

Description	Sealant	Bottle size	Operational Specs	Functions	Dimensions	Weight
Fully automatic single hose integrated system	SLX EG	450ml.	Mechanical operation durability: 500 cycles, full inflation, 3 min OFF time	<ul style="list-style-type: none"> <li>■ Full auto</li> <li>■ User interface on top</li> <li>■ Single hose</li> <li>■ Pictorial label with text</li> <li>■ Snap-together housing - no screws</li> </ul>	240mm x 160mm x 70mm 9 <sup>29</sup> / <sub>64</sub> " x 7 <sup>19</sup> / <sub>64</sub> " x 2 <sup>3</sup> / <sub>4</sub> "	1.76kg. 3.89lb.



### General Specifications

Fill time, 0-3Bar (44PSI)	Avg. 7.3m. for 255/75R17
Operational temperature	-40° to 55°C **
Operating voltage	12 V nominal
Current	15 amp max.
Power cord	3277mm
Airhose length	660mm
Gauge	0-6 BAR (0-90Psi)
Gauge illumination	LED Backlit
Warranty	6 years
Standards met	Chrysler, Ford

**Cutting edge technology.  
Top notch quality.**

**ITW Global Tire Repair USA**  
125 Venture Drive, Suite 210,  
San Luis Obispo, CA 93401  
Toll Free (888) 457 - 5463  
Fax (805) 489-1920

**ITW Global Tire Repair Europe GmbH**  
Carl-Benz-Strasse 10, D-88696  
Owingen, Germany  
Tel. +49 (0) 7551 - 9200-0  
Fax +49 (0) 75 51 / 92 00 - 990